



P112 SERIES

1. Operation Temperature Range : -40°C to +105°C
2. Dimensioning Shall Be Interpreted Per ANSI Y14.5M-1994
3. Contact Retention Force : 1.36kgf min. Per Contact

ORDERING INFORMATION

P112 - □□ - □□ - □□ - □□□□
No. of Single Row Pos. □
Housing Material □
Optional For Modification Code See Dwg No. 010 - 0004 - 420
Plating
 0 : Tin Plating Over All
 2 : Gold Flash
 6 : 30μ" Gold
 8 : 15μ" Gold

P112 - 12 - □ - □ - □□□□	12/24	51.6	50.00	46.20	55.6
P112 - 11 - □ - □ - □□□□	11/22	47.4	45.80	42.00	51.4
P112 - 10 - □ - □ - □□□□	10/20	43.2	41.60	37.80	47.2
P112 - 09 - □ - □ - □□□□	9/18	39.0	37.40	33.60	43.0
P112 - 08 - □ - □ - □□□□	8/16	34.8	33.20	29.40	38.8
P112 - 07 - □ - □ - □□□□	7/14	30.6	29.00	25.20	34.6
P112 - 06 - □ - □ - □□□□	6/12	26.4	24.80	21.00	30.4
P112 - 05 - □ - □ - □□□□	5/10	22.2	20.60	16.80	26.2
P112 - 04 - □ - □ - □□□□	4/8	18.0	16.40	12.60	22.0
P112 - 03 - □ - □ - □□□□	3/6	13.8	12.20	8.40	17.8
P112 - 02 - □ - □ - □□□□	2/4	9.6	8.00	4.20	13.6
P112 - 01 - □ - □ - □□□□	1/2	5.4	3.80		9.4
Part No.	No. of Pos.	Dim. A	Dim. B	Dim. C	Dim. D

ITEM	Q'TY	DESCRIPTION
②	1	Insulator : UL94V-0/2 Color : Natural or Ivory
①	BASE ON POS.	Contact : 100μ" Min. Tin Over All Or Selective Gold Plating Over 30μ" Nickel Plating
COMPONENT PARTS LIST		

Title : Customer Drawing Type : Power Connector

Part No. : P112 Series

Description : P112 Power Connector

CTL 彩電企業股份有限公司
CHARTRON INCORPORATION

Tolerances Unless Otherwise Specified :

X. ± 0.50	.X ± 0.38	.XX ± 0.25
X.° ±	.X° ±	.XX° ±

DWG No. : 010 - 0003 - 420	Date : 01 - Aug. - 2004		Dim.	Scale	Sheet	Rev.
APPD. : James C.	CHK. : Connie Z.		DRW. : Bryant C.	mm	N/A	1 of 1