



P200 SERIES

1. Operation Temperature Range : -40°C to +105°C
2. Dimensioning Shall Be Interpreted Per ANSI Y14.5M-1994
3. Contact Retention Force : 1.36kgf min. Per Contact

ORDERING INFORMATION

P200 - □□ - □ - □□□
 No. of Single Row Pos. | G2 : With Peg #1 & Peg #2

Plating

- 0 : 100μ" Min. Tin/Lead Plating Over All
- 2 : Gold Flash Over All
- 8 : 15μ" Min. Gold

Part No.	No. of Pos.	Dim. A	Dim. B	Dim. C	Dim. D	Dim. E
P200 - 12 - □ - □□	12/24	57.08	50.00	46.20	51.2	45.40
P200 - 10 - □ - □□	10/20	48.68	41.60	37.80	42.8	37.00
P200 - 09 - □ - □□	9/18	44.48	37.40	33.60	38.6	32.80
P200 - 08 - □ - □□	8/16	40.28	33.20	29.40	34.4	28.60
P200 - 07 - □ - □□	7/14	36.08	29.00	25.20	30.2	24.40
P200 - 06 - □ - □□	6/12	31.88	24.80	21.00	26.0	20.20
P200 - 05 - □ - □□	5/10	27.68	20.60	16.80	21.8	16.00
P200 - 03 - □ - □□	3/6	19.28	12.20	8.40	13.4	7.60
P200 - 02 - □ - □□	2/4	15.08	8.00	4.20	9.2	3.40

ITEM	Q'TY	DESCRIPTION
③	Base On Single Row Position	Contact : Brass 50μ" Min. Nickel Underplating
②	Base On Single Row Position	Contact : Brass 50μ" Min. Nickel Underplating
①	1	Insulator : Nylon 66 UL94V-0 Color : White

COMPONENT PARTS LIST

Title : Customer Drawing		Type : Power Connector	
Part No. : P200 Series			
Description : P200 Power Connector			
彩電企業股份有限公司 CHARTRON INCORPORATION			
Tolerances Unless Otherwise Specified :			
X. ± 0.50	.X ± 0.38	.XX ± 0.25	
X. ° ±	.X ° ±	.XX ° ±	
DWG No. : 010 - 0002 - 439	Date : 01 - Aug. - 2004		Dim. Scale Sheet Rev.
APPD. : James C.	CHK. : Connie Z.		DRW. : Bryant C.